



MINI WEDGE & G4

| | |
|-----------------|------------|
| WATTAGE | 1.2, 1.4 |
| LUMENS | 140-150 |
| KELVIN TEMP | 2700, 3000 |
| COLOR | N/A |
| CRI | 82 |
| OPERATING RANGE | 10-15VAC |
| BEAM ANGLES | OMNI |
| IP RATING | 65 |
| LIFESPAN | 40,000 HRS |
| WARRANTY | 5 YEARS |
| UL | UNKNOWN |
| FCC | UNKNOWN |

BRILLIANCE MICRO T-5 WEDGE & G-4 BIPIN

| | |
|-----------------|------------------------------------|
| WATTAGE | 1.2 |
| LUMENS | 100 |
| KELVIN TEMP | 2700 |
| COLOR | RED, GREEN, BLUE, AMBER (G-4 only) |
| CRI | 85 |
| OPERATING RANGE | 10-14VAC |
| BEAM ANGLES | OMNI |
| IP RATING | 65 |
| LIFESPAN | 35,000 HRS |
| WARRANTY | 3 YEARS |
| UL | YES |
| FCC | YES |



SCB, G4, WEDGE

| | |
|-----------------|------------|
| WATTAGE | 2.3-2.5 |
| *LUMENS | 250 |
| KELVIN TEMP | 2700, 3000 |
| COLORS | N/A |
| CRI | 82 |
| OPERATING RANGE | 10-18VAC |
| BEAM ANGLES | OMNI |
| IP RATING | UNKNOWN |
| LIFESPAN | 40,000 HRS |
| WARRANTY | 5 YEARS |
| UL | UNKNOWN |
| FCC | UNKNOWN |

BRILLIANCE BEACON SERIES

| | |
|-----------------|------------------------|
| WATTAGE | 2 |
| *LUMENS | 200 |
| KELVIN TEMP | 2200, 2700, 3000, 5700 |
| COLORS | N/A |
| CRI | 84 |
| OPERATING RANGE | 8-25VAC |
| BEAM ANGLES | OMNI |
| IP RATING | 65 |
| LIFESPAN | 35,000 HRS |
| WARRANTY | 5 YEARS |
| UL | YES |
| FCC | YES |



ROUND WAFER

| | |
|-----------------|------------|
| WATTAGE | 3.3 |
| *LUMENS | 200 |
| KELVIN TEMP | 2700 |
| COLORS | N/A |
| CRI | 82 |
| OPERATING RANGE | 12VAC |
| BEAM ANGLES | 100 |
| IP RATING | UNKNOWN |
| LIFESPAN | 25,000 HRS |
| WARRANTY | 5 YEARS |
| UL | UNKNOWN |
| FCC | UNKNOWN |

BRILLIANCE G-4 ROUND WAFER

| | |
|-----------------|------------|
| WATTAGE | 2 |
| *LUMENS | 120 |
| KELVIN TEMP | 2700 |
| COLORS | N/A |
| CRI | 85 |
| OPERATING RANGE | 8-25VAC |
| BEAM ANGLES | 180 |
| IP RATING | 60 |
| LIFESPAN | 35,000 HRS |
| WARRANTY | 5 YEARS |
| UL | YES |
| FCC | YES |



MR-11

| | |
|-----------------|------------|
| WATTAGE | 3 |
| *LUMENS | 230 |
| KELVIN TEMP | 2700, 5000 |
| COLORS | N/A |
| CRI | 82 |
| OPERATING RANGE | 10-18VAC |
| BEAM ANGLES | 22, 30 |
| IP RATING | UNKNOWN |
| LIFESPAN | 40,000 HRS |
| WARRANTY | 5 YEARS |
| UL | UNKNOWN |
| FCC | UNKNOWN |

BRILLIANCE MR-11

| | |
|-----------------|-------------------------|
| WATTAGE | 2 |
| *LUMENS | 120 |
| KELVIN TEMP | 2200, 2700, 3000, 5700 |
| COLORS | RED, GREEN, BLUE, AMBER |
| CRI | 85 |
| OPERATING RANGE | 8-25VAC |
| BEAM ANGLES | 15, 30, 60, 120 |
| IP RATING | 61 |
| LIFESPAN | 50,000 HRS |
| WARRANTY | 5 YEARS |
| UL | YES |
| FCC | YES |



* Lumens vary based on Kelvin temperature
 ** Halco is a trademark of Halco Lighting Technologies
 All Halco specs are from the Halco Lighting website



MR-16

| | |
|-----------------|-----------------------|
| WATTAGE | 2.5, 4, 4.5, 8 |
| *LUMENS | 200-660 |
| KELVIN TEMP | 2700, 3000, 5000 |
| COLORS | R, G, B, A (20° only) |
| CRI | 82 |
| OPERATING RANGE | 10-18VAC |
| BEAM ANGLES | 20, 40, 60 |
| IP RATING | UNKNOWN |
| LIFESPAN | 40,000 HRS |
| WARRANTY | 5 YEARS |
| UL | UNKNOWN |
| FCC | UNKNOWN |

BRILLIANCE MR-16

| | |
|-----------------|---|
| WATTAGE | 4, 5, 7 |
| *LUMENS | 260-560 |
| KELVIN TEMP | 2200, 2700, 3000, 5700 |
| COLORS | RED, GREEN, BLUE, AMBER (4 & 5 Watt only) |
| CRI | 85 |
| OPERATING RANGE | 8-25VAC |
| BEAM ANGLES | 15, 30, 60, 120 |
| IP RATING | 61 |
| LIFESPAN | 50,000 HRS |
| WARRANTY | 5 YEARS |
| UL | YES |
| FCC | YES |



PAR-36

| | |
|-----------------|---------------------------|
| WATTAGE | 6.5, 10, 18 |
| *LUMENS | 260-720 |
| KELVIN TEMP | 2700 |
| COLORS | R, G, B, A (10 Watt only) |
| CRI | 82 |
| OPERATING RANGE | 12VAC |
| BEAM ANGLES | 15, 20, 32 |
| IP RATING | 67 |
| LIFESPAN | UNKNOWN |
| WARRANTY | 5 YEARS |
| UL | UNKNOWN |
| FCC | UNKNOWN |

BRILLIANCE PAR-36

| | |
|-----------------|---|
| WATTAGE | 6, 9, 12 |
| *LUMENS | 380-920 |
| KELVIN TEMP | 2200, 2700, 3000, 5700 |
| COLORS | RED, GREEN, BLUE, AMBER (6 & 9 Watt only) |
| CRI | 85 |
| OPERATING RANGE | 8-25VAC |
| BEAM ANGLES | 15, 30, 60, 120 |
| IP RATING | 68 |
| LIFESPAN | 50,000 HRS |
| WARRANTY | 5 YEARS |
| UL | YES |
| FCC | YES |



* Lumens vary based on Kelvin temperature
 ** Halco is a trademark of Halco Lighting Technologies
 All Halco specs are from the Halco Lighting website